

System Overview

The Symmetry S830 Micro Proximity Reader reads HID 125KHz proximity cards and its small size makes it ideal for mounting unobtrusively.

The Symmetry S830 can be connected to the complete multiNODE range of database and door controllers.

Unlike Wiegand interface readers, the Symmetry S830 uses secure, bi-directional, pseudo-random supervised communications between the multiNODE controllers and their associated readers. An alarm will sound if communications are lost.

A distance from any of the multiNODE controllers to the Symmetry S830 reader of up to 3000 feet (1000m) can also be achieved.

The Symmetry S830 has a typical read range of up to 2.5" (62mm) with HID Proxcard II.

The Symmetry S830 is available in three colors - ash gray, charcoal gray and black.

Other key features include LEDs for visual indication of card accepted or card rejected and an integrated buzzer for card read and door pre-held warning.

The Symmetry S830 Micro Proximity Reader is very cost effective and comes with exceptional reliability and consistent read range characteristics.

The Symmetry S830 reader has fully potted electronics making it ideal for both outdoor and indoor use. It is warranted against defects in workmanship for life (see our warranty policy for details).



Key Features

- Small size allows unobtrusive installation
- Reads HID 125KHz proximity cards
- Typical read range is up to 2.5" (62mm) with HID ProxCard II
- Visual indication is via LEDs for card accepted and card rejected
- Integrated buzzer for confirmation of card read and door pre-held warning is included
- Secure, bi-directional, pseudo-random supervised communications
- Rugged polycarbonate design has potted electronics - ideal for both outdoor and indoor applications
- Comes with a lifetime warranty

Section Heading

Model Types

Model S830 - Card Only Micro Proximity Reader

- Available in ash gray, charcoal gray and black

Power Requirements

- Nominal 12VDC (9-14V)
- Maximum current consumption 0.1 Amp

Communicating Distances

- multiNODE-1000/multiNODE-2 SMD/multiNODE2000/
multiNODE-2100 controllers / multiNODE-2150 controllers
- to Symmetry S830 (current loop) = 3000ft/1000m

Operating Environment

- -13°F to +158°F (-25°C to +70°C)
- 0% to 95% Humidity, non condensing

Dimensions Inches (mm)

- Width = 1.8" (45mm)
- Height = 3.1" (78mm)
- Depth = 0.7" (18mm)

Approvals

Radio regulatory approvals to:

- FCC CFR47 Part 15.209
- EN 300 330 – 1 v1.3.1

EMC Type Testing

- EN50130-4

Access control product testing

- EN 50133-1:1997



AMAG Technology Inc. is a subsidiary of Group 4 Technology Ltd.
©COPYRIGHT AMAG TECHNOLOGY INC. 2006

AMAG is a Microsoft Gold Certified Partner for Security Solutions. Symmetry is a registered trademark of Group 4 Technology Ltd. ENVIS is a trademark of Group 4 Technology Ltd. TLM is a registered trademark of Group 4 Technology Ltd. Microsoft is a registered trademark of Microsoft Corporation. All other brand names and product names are trademarks or registered trademarks of their respective owners.

Information contained in this literature is representative only and does not form part of a contract. Our policy is one of continuous product improvement and details may vary without notification. We are committed to providing defect-free products and services to our customers in partnership with equally committed suppliers and authorized dealers.