



FT8308/FR8308 Fiber Transmitter and Receiver

EIGHT-CHANNEL DIGITALLY ENCODED VIDEO

Product Features

- 8-Bit Digitally Encoded Video for High-Quality Multi-Channel Video Transmission over a Single Fiber
- Multimode Fiber Support for Distances up to 1 km
- Single-Mode Fiber Support for Distances up to 30 km
- Exceeds All Requirements for the RS-250C Medium-Haul Transmission Specification
- Compatible with NTSC, PAL, and SECAM Video Standards
- Meets NEMA TS 2 and Caltrans Traffic Signal Control Equipment Environmental Standards
- No Performance Adjustments Required
- 12 VDC or 24 VAC Power Supply
- Standalone and Rack-Mountable Modular Design
- LED Indicators for Monitoring of Signal Status and Operating Power



The **FT8308/FR8308** fiber transmitter and receiver provide the ability to transmit up to eight composite video channels over one optical fiber. The **FT8308** transmitter and the **FR8308** receiver are available in multimode and single-mode versions.

Modular in design, the **FT8308** and **FR8308** units can be rack mounted or can be used as standalone modules. Rack mounting is accomplished using the RK5000 Series rack mount chassis. Standalone modules can be placed on a desktop or can be mounted to a wall.



TECHNICAL SPECIFICATIONS

MODELS

Model No.		Fiber Optic Connector Type	Wavelength	Optical Power Budget	Maximum Transmission Distance
Transmitter	Compatible Receiver				
Multimode (62.5/125 μm)					
FT8308MSTR	FR8308MSTR	ST	1310 nm	20 dB*	1 km (0.6 mi) [†]
Single-Mode (9/125 μm)					
FT8308SSTR	FR8308SSTR	ST	1310 nm	20 dB	30 km (18.6 mi) ^{††}
FT8308SFCR	FR8308SFCR	FC	1310 nm	20 dB	30 km (18.6 mi) ^{††}

*When using 50/125 μ m multimode fiber, subtract 3 dB from the optical power budget.
[†]Maximum transmission distance is limited by fiber bandwidth.
^{††}Maximum transmission distance is based on attenuation of 0.5 dB/km plus a 5 dB buffer for connector and splice losses.

Notes:

- For conformed coated models, replace the first letter *F* in the model number with the letter *C*. The conformed coated version of FT8308MSTR, for example, is CT8308MSTR.
- For models with higher optical power budgets, contact the factory.

Supplied Accessories

- Regulated switching power supply with multiple plug adapters (North American, Australian, United Kingdom, and European); 100-240 VAC, 50-60 Hz input, 12 VDC output
Note: In extreme temperature conditions, it is recommended that an industrial-rated outdoor power supply such as the Pelco[®] WCS1-4 power supply be used.
- Wall clip for attachment of single module to wall

VIDEO

Number of Channels	8
Modulation Type	Pulse code modulation, 8-bit resolution
Video Input	1.0 Vp-p, 75 ohms; NTSC, PAL, and SECAM
Bandwidth	6.5 MHz
Gain	Unity
Crosstalk	-50 dB typical at 3.58 MHz
Differential Gain	<1%
Differential Phase	<1.2°
Tilt	<1%
Signal-to-Noise Ratio	>60 dB (CCIR weighted)

GENERAL

Operating Temperature	-40° to 167°F (-40° to 75°C)
Input Power Requirements	12 VDC or 24 VAC, 460 mA
LED Indicators	
Transmitter	Power Video Present (per channel)
Receiver	Power Video Present (per channel) Optic Fault
Dimensions	8.75" D x 2.28" W x 4.81" H (22.23 x 5.79 x 12.22 cm)
Unit Weight	2.56 lb (1.16 kg)
Shipping Weight	4 lb (1.81 kg)

MECHANICAL

Connectors	
Video	BNC (per channel)
Rack Power/Alarm	4-pin connector
Standalone Power	2-pin connector, screw terminal
Fiber Optic	ST for multimode fiber ST or FC for single-mode fiber

CERTIFICATIONS

- CE, Class A
 - UL Listed
 - UL Listed to Canadian safety standards
 - FCC, Class A
 - C-Tick
 - Complies with FDA requirements for Class 1 laser products
 - Meets NEMA TS 2 and Caltrans traffic signal control equipment standards for ambient operating temperature, mechanical shock and vibration, humidity with condensation, high-line/low-line voltage conditions, and transient voltage protection—certified by an independent testing laboratory
- Note:** Conformal coating is required for operation in environments with relative humidity above 95% (condensing).

OPTIONAL ACCESSORIES

WM5002-3U	Wall mount base kit for double-width module
WM5002-3UEXP	Wall mount expansion kit for double-width module
RK5000-3U	19-inch rack mount chassis for 14 slots, no power (3 RUs)
RK5000PS-3U	19-inch rack mount chassis for 12 slots with power (3 RUs)
EPS5000-120	External rack power supply, 1 RU, dual 120 W power outputs
RK5001B-3U	Blank filler panel, single width
RK5002B-3U	Blank filler panel, double width
RK5002-1UEXP	Adapter kit that allows a 3 RU double-width fiber module to be used in RK5000PS-5U rack mount chassis



Pelco Worldwide Headquarters:

3500 Pelco Way, Clovis, California 93612-5699 USA
USA & Canada Tel: (800) 289-9100 • FAX (800) 289-9150
International Tel: (559) 292-1981 • FAX (559) 348-1120
www.pelco.com

Pelco and the Pelco logo are registered trademarks of Pelco.
 Specifications subject to change without notice.
 ©Copyright 2006, Pelco. All rights reserved.